

E.P.R. Hand Pull Valve



ORDERING CODE

4H	2	10	-	06	L
Specification Code	Series Code	Number of Places		Joint Pipe Bore	Type Code
4H 5 ways/2 (3) positions	Series 200 Series 300 Series 400	10 Single head double position 20 Single head three position		06 : 1/8" 15 : 1/4" 15 : 3/8" 15 : 1/2"	Blank 5/3 reset tye L 5/3 Locking type

Specifications

MODEL	4H210-06	4H210-08	4H230-08	4H310-08	4H310-10	4H330-10	4H410-15	4H430-15
Working medium	40µ Filtered air							
Motion pattern	Direct Drive type							
Effective Section Area	14mm ² (cv=0.78)	16mm ² (cv=0.89)	12mm ² (cv=0.67)	25mm ² (cv=1.4)	30mm ² (cv=1.68)	18mm ² (cv=1.00)	50mm ² (cv=2.79)	30mm ² (cv=1.68)
Joint pipe bore	Air inlet - Air outlet - Exhaust = 1/8"	Air inlet - Air outlet = 1/4" - Exhaust = 1/8"		Air inlet - Air outlet - Exhaust = 1/4"	Air inlet - Air outlet = 3/8" - Exhaust = 1/4"		Air inlet - Air outlet - Exhaust = 1/2"	
Working pressure	0 – 8 bar							
Operating temperature	0° - 60 ° C							